

Link do produktu: <https://vipelektrogadzet.pl/dell-ultrasharp-49-curved-monitor-u4924dw-p-235298.html>

DELL ULTRASHARP 49 CURVED MONITOR - U4924DW

Cena	5 429,00 zł
Dostępność	Dostępny
Numer katalogowy	IM-DE210-BGTX
Kod producenta	210-BGTX
Kod EAN	5397184657133

Opis produktu

Display diagonal	49 "
Display resolution	5120 x 1440 pixels
HD type	5K Ultra HD
Touchscreen	No
Viewing angle, vertical	178 °
Viewing angle, horizontal	178 °
Response time	14 ms
Panel type	IPS
Contrast ratio (typical)	2000:1
Display number of colours	1.07 billion colours
Pixel pitch	0.234 x 0.234 mm
Native aspect ratio	32:9
Screen shape	Curved
Display technology	LCD
Backlight type	LED
Supported graphics resolutions	640 x 400,640 x 480 (VGA),720 x 400,800 x 600 (SVGA),1024 x 768 (XGA),1152 x 864 (XGA+),1280 x 1024 (SXGA),1600 x 900,1920 x 1080 (HD 1080),2560 x 1080,2560 x 1440,3840 x 1080,5120 x 1440
Horizontal scan range	25 - 115 kHz
Display diagonal (metric)	124.46 cm
Vertical scan range	24 - 86 Hz
High Dynamic Range (HDR) supported	No
Supported video modes	480p,576p,720p,1080i,1080p
Colour gamut	98 %
Colour depth	10 bit
Surface hardness	3H
Anti-glare screen	Yes
Maximum refresh rate	60 Hz
Display brightness (typical)	350 cd/m ²
Viewable size, vertical	336.96 mm
Viewable size, horizontal	1198.08 mm
Pixel density	109 ppi
sRGB coverage (typical)	100 %
Response time (fast)	5 ms
Colour gamut standard	DCI-P3
Viewable size diagonal	1244.6 mm
Screen curvature rating	3800R
Wydajność AMD FreeSync	No
NVIDIA G-SYNC	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia Built-in speaker(s)	Yes
RMS rated power	18 W

	Number of speakers	2
	Built-in camera	No
Konstrukcja	Product colour	Black,Silver
	Market positioning	Office
	Feet colour	Silver
	Front bezel colour	Black
	Detachable stand	Yes
	Heavy metals free	Hg (mercury)
Porty i interfejsy	DisplayPorts quantity	1
	USB Power Delivery up to	90 W
	HDMI ports quantity	2
	HDMI version	2.1
	DisplayPort version	1.4
	USB Type-C DisplayPort Alternate Mode	Yes
	USB Power Delivery (USB PD)	Yes
	HDCP	Yes
	HDCP version	2.2
	Built-in USB hub	Yes
	HDMI	Yes
	Headphone out	Yes
	USB Type-A downstream ports quantity	5
	USB hub version	3.2 Gen 2 (3.1 Gen 2)
	USB upstream port type	USB Type-C
	AC (power) in	Yes
	Number of USB Type-C upstream ports quantity	2
	USB Type-C downstream ports quantity	2
	Built-in KVM switch	Yes
Sieć Wi-Fi		No
Ergonomia	VESA mounting	Yes
	Cable lock slot type	Kensington
	Plug and Play	Yes
	Tilt angle range	-5 - 21 °
	Panel mounting interface	100 x 100,200 x 100 mm
	LED indicators	Yes
	On Screen Display (OSD)	Yes
	Picture-in-Picture	Yes
	Cable lock slot	Yes
	Height adjustment	Yes
	Tilt adjustment	Yes
	Swivelling	Yes
	Pivot	No
	Swivel angle range	-170 - 170 °
	Adjustable height (max)	120 mm
Moc	AC input voltage	100 - 240 V
	AC input frequency	50 - 60 Hz
	Power supply type	Internal
	Input current	3.6 A
	Power consumption (max)	290 W
	Power consumption (standby)	0.3 W
	Power consumption (typical)	45 W
	Energy efficiency class (SDR)	G
	Energy consumption (SDR) per 1000 hours	45 kWh
	Power consumption (off)	0.3 W
	Energy efficiency scale	A to G
	Energy efficiency class (HDR)	Not available
	European Product Registry for Energy Labelling (EPREL) code	1367150
Warunki pracy	Operating temperature (T-T)	0 - 40 °C
	Operating relative humidity (H-H)	10 - 80 %
	Storage temperature (T-T)	-20 - 60 °C
	Storage relative humidity (H-H)	5 - 90 %
	Operating altitude	0 - 5000 m
	Non-operating altitude	5000 - 12192 m
Zawartość opakowania	Cables included	AC,DisplayPort,HDMI,USB Type-A to USB Type-C,USB Type-C
	Quick start guide	Yes
	Stand included	Yes
	DisplayPort cable length	1.8 m
	HDMI cable length	1.8 m

Waga i rozmiary	Bezel width (side)	11 mm
	Bezel width (top)	12.09 mm
	Bezel width (bottom)	16.9 mm
	Width (without stand)	1214.9 mm
	Height (without stand)	365.95 mm
	Depth (without stand)	112.09 mm
	Width (with stand)	1214.9 mm
	Depth (with stand)	269.14 mm
	Weight (with stand)	16300 g
	Height (with stand)	520.57 mm
	Weight (without stand)	12150 g
Dane opakowania	Package weight	27730 g
	Package width	530.4 mm
	Package height	346.5 mm
	Package depth	1422.4 mm
Szanse na przetrwanie	Sustainability certificates	ENERGY STAR,TCO
	Doesn't contain	PVC/BFR
Carbon footprint	Carbon emissions, energy usage (kg of CO2e)	455
	Carbon emissions, manufacturing (kg of CO2e)	536.1
	Carbon emissions, logistics (kg of CO2e)	136
	Carbon emissions, end-of-life (kg of CO2e)	15.8
	Total carbon footprint (kg of CO2e)	1140
	PAIA version	1.3.1, 2022
	Total carbon emissions, standard deviation (kg of CO2e)	318
Szczegóły Techniczne	Compliance certificates	RoHS
Pozostałe funkcje	Ethernet LAN (RJ-45) ports	1