

Link do produktu: <https://vipelektrogadzet.pl/monitor-viewsonic-cde6530-65-4k-presentation-display-digital-signage-p-242305.html>



Monitor ViewSonic CDE6530 65" 4K Presentation Display Digital Signage

Cena	6 033,62 zł
Numer katalogowy	INC-DSVSLD650010
Kod producenta	CDE6530
Kod EAN	0766907017489

Opis produktu

Parametry

- **Przekątna ekranu:** 65.00 cali
- **Jasność matrycy:** 500 cd/m²
- **Typ matrycy:** VA
- **Rozdzielczość maksymalna:** 3840 x 2160 (4K UHD)
- **Kontrast statyczny:** 1200 :1
- **Touch:** Nie
- **System operacyjny:** Android 11
- **Montaż VESA:** 600 x 400
- **Wbudowane głośniki:** 2 x 16W
- **Złącze HDMI:** HDMI x4
- **Złącze RS-232:** Tak
- **Wymiary [S x W x G] (mm):** 1463,3 x 838,3 x 81,6
- **Waga netto (kg):** 25.400
- **Rozmiar ramki (T/L/R/B) [mm]:** 14.7/14.7/14.7/14.7
- **Tryb portretowy:** Tak
- **Tryb panoramiczny:** Tak
- **Tryb pracy:** 24h/7
- **Informacje dodatkowe:** Type/ Tech: TFT LCD Module. VA type, DLED backlight, Aspect Ratio: 16:9, Colors: 1.07G (8bits + FRC-), Contrast Ratio: 1200:1 (typ.), 5000:1 (DCR enabled), Response Time: 6.5ms, Viewing Angles: H = 178, V = 178 typ., Backlight Life: 50,000 hours, Surface Treatment: Anti-Glaire, 3H hardness, Haze 25%, Disclaimer: 50,000 hours backlight life at 8 hours of use per day, Processor: Quad-core ARM Cortex A55, RAM: 4GB, Storage: 32GB, INPUT HDMI: 2.1x3 (3840x2160 @60Hz, HDMI 1 support ARC), OUTPUT HDMI: 2.0 x1 (3840x2160 @60Hz), WiFi Slot: x 1, OPS Slot:, RJ45: x 1, USB Type A: 2.0 x 1, 3.0 x 1, USB Type C: x1 (DP1.2, PD 65W, USB2.0, 100M ethernet), Voltage: 100-240 VAC +/- 10%, Consumption: 88 W(typ.) < 0.5W(off), Temperature (o C): 0 to 40°C, Humidity: 10%-90% RH, REGULATIONS: cTUVus, FCC/ICES003, Energy star 8.0, EPEAT, Mexico NOM , Mexico Energy, EMC/CE , CB, EAC, UkrSEPRO, RCM, LBL, Flicker free, Green BOM, RoHS , ErP, REACH, SCIP, WEEE , Annex I, Annex II, TPCH , Packing waste,, CA65
- **Gwarancja producenta [mies.]:** 36