

Link do produktu: <https://vipelektrogadzet.pl/plyta-asrock-b860m-livemixer-wifi-b860ddr5sata3m2tb4/wifibtpcie50s1851m-atx-p-243766.html>



## Płyta ASRock B860M LiveMixer WiFi /B860/DDR5/SATA3/M.2/TB4/WiFi/BT/PCIe5.0/s.1851/M-ATX

Cena	<b>662,39 zł</b>
Numer katalogowy	<b>INC-PGARIDID9090</b>
Kod producenta	<b>B860M LiveMixer WiFi</b>
Kod EAN	<b>4711581490314</b>

### Opis produktu

#### Parametry

- **Gniazdo procesora:** Socket 1851
- **Obsługiwane typy procesorów:** Intel Core Ultra Processors (series 2)
- **Uwagi do procesora:** - Supports Intel® Hybrid Technology, - Supports Intel® Turbo Boost Max 3.0 Technology, - Supports Intel® Thermal Velocity Boost (TVB), - Supports Intel® Adaptive Boost Technology (ABT), - Integrated NPU for dedicated AI acceleration
- **Format płyty:** Micro-ATX
- **BIOS:** 256Mb AMI UEFI Legal BIOS with GUI support
- **Chipset płyty głównej:** Intel® B860
- **Ilość złącz pamięci DDR5:** 4
- **Maksymalna wielkość pamięci:** 256 GB
- **Tryb pracy pamięci RAM:** Dual Channel
- **Standard pamięci:** DDR5-8666+ (OC)
- **Uwagi do pamięci RAM:** - Supports DDR5 non-ECC, un-buffered memory up to 8666+(OC), - 1DPC 1R Up to 8666+ MHz (OC), 5600 MHz Natively, - 1DPC 2R Up to 6800+ MHz (OC), 5600 MHz Natively, - 2DPC 1R Up to 6533+ MHz (OC), 4800 MHz Natively, - 2DPC 2R Up to 5600+ MHz (OC), 4400 MHz Natively, - Supports Clocked Unbuffered DIMM (CUDIMM), - Supports Intel® Extreme Memory Profile (XMP) 3.0x
- **Zintegrowany kontroler SATA:** Chipset+CPU: 4x SATA III 6Gb/s - RAID 0,1,10,5 + 3x M.2
- **Uwagi do kontrolera SATA:** CPU:, - 1 x Blazing M.2 Socket (M2\_1, Key M), supports type 2280 PCIe Gen5x4, (128 Gb/s) mode, Chipset:, - 1 x Hyper M.2 Socket (M2\_2, Key M), supports type 2280 PCIe Gen4x4, (64 Gb/s) mode, - 1 x Hyper M.2 Socket (M2\_3, Key M), supports type 2280 PCIe Gen4x4, - 4 x SATA3 6.0 Gb/s Connectors, Supports Intel® Volume Management Device (VMD), Supports NVMe SSD as boot disks
- **Wbudowana karta graficzna:** Intel® Xe LPG Graphics Architecture
- **Gniazda karty graficznej:** HDMI, Thunderbolt™ 4
- **Uwagi do karty graficznej:** - 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max., resolution up to 4K 120Hz, - 1 x Intel® Thunderbolt™ 4, supports HDCP 2.3 and max. resolution up to, 8K 60Hz / 5K 120Hz, Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported, only with processors which are GPU integrated, Supports two 4K displays or one 8K display, Only the CPU's embedded graphics can be displayed through Thunderbolt™ port
- **Zintegrowana karta dźwiękowa:** Realtek ALC1220P 7.1 Surround Sound High Definition Audio CODEC
- **Gniazda karty dźwiękowej:** 3x Audio Jack, Wewnętrzne gniazdo audio przedniego panelu
- **Uwagi do karty dźwiękowej:** - Impedance Sensing on Rear Out port, - Individual PCB Layers for R/L Audio Channel, - Nahimic Audio
- **Złącza PCI Express x16:** 1
- **Złącza PCI Express x4:** 1
- **Uwagi do złącz PCI:** CPU:, - 1 x PCIe 5.0 x16 Slot (PCIE1), supports x16 mode, Chipset:, - 1 x PCIe 4.0 x4 Slot (PCIE2), supports x4 mode, - 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module and, Intel® CNVio/CNVio2 (Integrated WiFi/BT), Supports NVMe SSD as boot disks
- **Port LAN:** 1x 2,5 Gigabit LAN 10/100/1000/2500 Mb/s (Dragon RTL8125BG)
- **Uwagi do karty sieciowej:** - Supports Dragon 2.5G LAN Software, - Smart Auto Adjust Bandwidth Control, - Visual User Friendly UI, - Visual Network Usage Statistics, - Optimized Default Setting for Game, Browser, and Streaming Modes, - User Customized Priority Control

- 
- **Maksymalna ilość portów USB 2.0:** 10
  - **Maksymalna ilość portów USB 3.x:** 11
  - **Maksymalna ilość portów USB 4.0:** 1
  - **Porty USB na panelu tylnym:** 6x USB 2.0 + 6x USB 3.0 + 1x Thunderbolt 4
  - **Gniazda USB na płycie głównej:** 2x USB 2.0 (4 porty) + 2x USB 3.0 (4 porty) + 1x USB 3.0 Type-C (1 port)
  - **Port Wi-Fi:** IEEE 802.11a/b/g/n/ac/ax/axe
  - **Port Bluetooth:** Bluetooth V5.3
  - **Uwagi do WiFi / BT:** - 802.11axe Wi-Fi 6E Module, - Supports Dual-Band 2x2 with extended 6GHz band\* support, - 2 antennas to support 2 (Transmit) x 2 (Receive) diversity technology, - Supports MU-MIMO
  - **Port PS/2:** Brak
  - **Port szeregowy (COM):** Brak
  - **Port równoległy (LPT):** Brak
  - **Inne porty i gniazda:** Thermal Sensor connectors, SPI TPM header (14-1pin), Power LED and Speaker Header, RGB LED Header, 3x Addressable LED Headers, 2x CPU Fan connector(s), 3x Chassis Fan Connectors, AIO Pump Fan Connector, 2x Antenna Ports, BIOS FlashBack button
  - **Gniazdo zasilania:** ATX (24-pin) + 2x ATX12V (8-pin)
  - **Wymiary [S x W] (mm):** 244 x 244
  - **Opakowanie:** BOX
  - **Wyposażenie dodatkowe:** - 2 x SATA Data Cables, - 2 x ASRock WiFi 2.4/5/6 GHz Antennas, - 1 x Thermistor Cable
  - **Zawiera baterię / akumulator:** Tak
  - **Informacje dodatkowe:** Operating System: Microsoft Windows® 11 64-bit