

Link do produktu: <https://vipelektrogadzet.pl/plyta-gigabyte-b860-a-elite-wf7-ice-b860ddr5sata3m2usb4wifibtpcie50s1851atx-p-243835.html>



Płyta Gigabyte B860 A ELITE WF7 ICE / B860/DDR5/SATA3/M.2/USB4/WiFi/BT/PCIe5.0/s.1851/ATX

Cena	941,17 zł
Numer katalogowy	INC-PGGBIDID9000
Kod producenta	B860 A ELITE WF7 ICE
Kod EAN	4719331866846

Opis produktu

Parametry

- **Gniazdo procesora:** Socket 1851
- **Obsługiwane typy procesorów:** Intel Core Ultra Processors (series 2)
- **Uwagi do procesora:** L3 cache varies with CPU
- **Format płyty:** ATX
- **BIOS:** 256 Mbit flash
- **Chipset płyty głównej:** Intel® B860
- **Ilość złącz pamięci DDR5:** 4
- **Maksymalna wielkość pamięci:** 256 GB
- **Tryb pracy pamięci RAM:** Dual Channel
- **Standard pamięci:** DDR5-9200 (OC), DDR5-8800 (OC), DDR5-8600 (OC), DDR5-8400 (OC), DDR5-8266 (OC), DDR5-8200 (OC), DDR5-8000 (OC), DDR5-7950 (OC), DDR5-7900 (OC), DDR5-7800 (OC), DDR5-7600 (OC), DDR5-7400 (OC), DDR5-7200 (OC), DDR5-7000 (OC), DDR5-6800 (OC), DDR5-6600 (OC), DDR5-6400, DDR5-5600
- **Uwagi do pamięci RAM:** Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules, (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules, Support for Extreme Memory Profile (XMP) memory modules
- **Zintegrowany kontroler SATA:** Chipset+CPU: 4x SATA III 6Gb/s - RAID 0,1,5,10 + 3x M.2
- **Uwagi do kontrolera SATA:** CPU:; - 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280, PCIe 5.0x4/x2 SSD support) (M2A_CPU), Chipset:; - 2 x M.2 connectors (Socket 3, M key, type 22110/2280, PCIe 4.0 x4/x2 SSD support) (M2Q_SB, M2N_SB), - 4x SATA 6Gb/s connectors
- **Gniazda karty graficznej:** 2x HDMI, USB4 Type-C, DisplayPort
- **Uwagi do karty graficznej:** - 1 x USB4® USB Type-C® port, supporting USB4 and DisplayPort video outputs, and a maximum resolution of 3840x2160@144 Hz, - Support for DisplayPort 2.1 version, - 1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz, - 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz, - Support for HDMI 2.1 version and HDCP 2.3, - 1 x front HDMI port, supporting a maximum resolution of 1920x1080@30 Hz, - Support for HDMI 1.4 version(Graphics specifications may vary depending o, - Support for up to quad-display at the same time
- **Zintegrowana karta dźwiękowa:** Realtek® HD Audio CODEC
- **Gniazda karty dźwiękowej:** Wyjście optyczne S/PDIF, 2x Audio Jack, Wewnętrzne gniazdo audio przedniego panelu
- **Uwagi do karty dźwiękowej:** High Definition Audio, 2/4/5.1/7.1-channel
- **Złącza PCI Express x16:** 3
- **Uwagi do złącz PCI:** CPU:; - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 PCIEX16, - The PCIEX16 slot can only support a graphics card or an NVMe SSD, - If only one graphics card is to be installed, be sure to install it in, the PCIEX16 slot, Chipset:; - 2 x PCI Express x16 slots, supporting PCIe 4.0 and running at x1, (PCIEX1_1, PCIEX1_2)
- **Port LAN:** 1x 2,5 Gigabit LAN 100/1000/2500 Mb/s (Realtek®)
- **Uwagi do karty sieciowej:**
- **Maksymalna ilość portów USB 2.0:** 8
- **Maksymalna ilość portów USB 3.x:** 9
- **Maksymalna ilość portów USB 4.0:** 1
- **Porty USB na panelu tylnym:** 4x USB 2.0 + 4x USB 3.0 + 2x USB 3.1 + 1x USB 4
- **Gniazda USB na płycie głównej:** 4x USB 2.0 + 2x USB 3.0 + 1x USB 3.1 Type-C
- **Port Wi-Fi:** IEEE 802.11a/b/g/n/ac/ax/be

-
- **Port Bluetooth:** Bluetooth V5.4
 - **Uwagi do WiFi / BT:** Realtek® Wi-Fi 7 RTL8922AE (PCB rev. 1.0), - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency, bands, - BLUETOOTH 5.4, - Support for 11be 320MHz wireless standard, MediaTek Wi-Fi 7 MT7925 (PCB rev. 1.1), - Actual data rate may vary depending on environment and equipment, - Wi-Fi 7 features require Windows 11 SV3 to function properly, - Wi-Fi 7 channels on 6 GHz band availability depends on country's regulati
 - **Port PS/2:** Brak
 - **Port szeregowy (COM):** Brak
 - **Port równoległy (LPT):** Brak
 - **Inne porty i gniazda:** CPU fan header, CPU fan/water cooling pump header, 3x system fan headers, System fan/water cooling pump extension cable header, 3x Addressable RGB Gen2 LED strip headers, RGB LED strip header, Front panel header, Front Panel Audio header (AAFP), Trusted Platform Module header, Power-on button(s), Reset button, Q-Flash Plus button, Reset jumper, Clear CMOS jumper, 2x SMA antenna connectors (2T2R)
 - **Gniazdo zasilania:** ATX (24-pin) + 2x ATX12V (8-pin)
 - **Wymiary [S x W] (mm):** 305 x 244
 - **Opakowanie:** BOX
 - **Wyposażenie dodatkowe:**
 - **Zawiera baterię / akumulator:** Tak
 - **Informacje dodatkowe:** Norton® Internet Security (OEM version), LAN bandwidth management software, Support for Windows 11 64-bit, BIOS: PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0